

COMPANY: \_\_\_\_\_  
 JOB REF: \_\_\_\_\_  
 ATTENTION: \_\_\_\_\_

BASIN SIZE: \_\_\_\_\_ X \_\_\_\_\_  
 -100     -200     -300     -400  
 -201     -301     -401

VALVE BOX SIZE: \_\_\_\_\_ X \_\_\_\_\_  
 ATTACHED     DETACHED

COVER DESCRIPTION:     HINGED DOOR     VALVE BOX     SOLID

COVER THICKNESS: \_\_\_\_\_  
 (IF NOT STANDARD)     ALUMINUM     FIBERGLASS  
 STEEL

COVER COATING:     STANDARD     EPOXY     GALVANIZED

STUDS:     SIMPLEX     DUPLEX     TRIPLEX

DISCONNECT DESCRIPTION:     AK SS RAIL SYSTEM

PUMP: \_\_\_\_\_  
 AK/FREE FLOW

VERTICAL     HORIZONTAL     OTHER \_\_\_\_\_

DISCHARGE TYPE:     COMMON     PARALLEL  
 THRU COVER     THRU WALL

DISCHARGE FITTING:     STAINLESS STEEL     ENVIRONBOOT  
 LINK SEALS     OTHER \_\_\_\_\_

SIZE: \_\_\_\_\_  
 PVC     SS     GALV.     DUCTILE IRON

GUIDE RAILS:     STAINLESS STEEL     GALVANIZED  
 SIZE: \_\_\_\_\_

VALVE TYPE:     GATES     PLUGS     TRUE UNION  
 FLANGED     THREADED     OTHER \_\_\_\_\_

CHECK VALVE TYPE:     PVC     CAST IRON     BRASS  
 OTHER \_\_\_\_\_

ELECTRICAL COUPLING:  
 SIZE: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_

JUNCTION BOX:     YES    OR     NO

INLET FITTING:     CAST IRON HUB     ADAPT-A-FLEX  
 SIZE: \_\_\_\_\_  
 SCH: \_\_\_\_\_  
 OTHER \_\_\_\_\_